



Newland AIDC
Scanning Made Simple



NLS-NVH300-DP

HANDHELD INDUSTRIAL DPM BARCODE SCANNER

FEATURES

Excellent DPM Decoding Capability

Featuring the latest UIMG[®] decoding system, it enhances decoding success rates for complex barcodes, optimizing workflows and improving overall decoding efficiency. It also delivers exceptional decoding performance for DPM barcodes, including laser-etched and dot-peened markings.

Advanced Illumination system

Provide white direct illumination, red and blue diffuse ring lights, rich lighting system can meet different materials (such as reflection), shape (curved surface), background and bar code color of all kinds of complex scanning code needs.

AI Function and Intelligent Learning

Equipped with the latest AI-powered barcode positioning technology, the NLS-NVH300 improves decoding performance for low-contrast barcodes. Additionally, intelligent learning enables automatic parameter adjustments based on different scenarios.

High Protection Industrial Structure Design

The NLS-NVH300, built into an IP64-sealed and can withstand repeated falls from 2.4 meters to the ground, with excellent reliability and stability.



2D Barcode



1D Barcode



NSet



RS232



USB



2.4m
Drop

NLS-NVH300-DP

Performance

Image Sensor		1280 × 960 CMOS
Illumination		Direct: white light LEDs; Diffuse: Ring of red&blue LEDs;
Aiming		650nm laser diode
Symbologies	2D	QR Code, PDF417, Micro QR, Data Matrix, AZTEC.
	1D	EAN-13,EAN-8, UPC-A, UPC-E, ISSN, ISBN, Codabar, Code128,Code93, ITF-6,ITF-14, Interleaved 2 of 5, Industrial 2 of 5, Standard 2 of 5, Matrix 2 of 5, Code 39
Resolution*		1D ≥1.67mil 2D≥3mil
Product Type		NLS-NVH300-V2-DP
	Code 39 3.3mil	10mm-100mm
	Code 39 5mil	10mm-130mm
Typical Depth of Field*	Data Matrix 5mil	25mm-90mm
	Data Matrix 10mil	0mm-130mm
	QR Code 5mil	10mm-85mm
	QR Code 15mil	0mm-170mm
Min. Symbol Contrast*		15%
Scan Angle**		Roll: 360°, Pitch: ±60°, Skew: ±55°
Field of View		Horizontal 41°, Vertical 31°

Physical

Interface		USB,RS232,Ethernet
Operating Voltage		5VDC±5%
Rated Power Consumption		2190mW (typical)
Current@5VDC	operating(typical)	438mA
	operating(max.)	476mA
Dimensions		76(W) ×107(D) ×185(H) mm
Weight		245g
Notification		Beep, LED indicator, Vibrator

Environmental

Operating Temperature		-20°C to 50°C(-4°F to 122°F)
Storage Temperature		-40°C to 70°C(-40°F to 158°F)
Humidity		5% to 95% (non-condensing)
ESD		±16 KV (air discharge); ±8 KV (direct discharge)
Drop		2.4m
Sealing		IP64
Certifications		FCC Part15 Class B, CE EMC Class B, BIS
Accessories	USB	Used to connect the NVH300 to a host device.
	Cable	RS-232 Used to connect the NVH300 to a host device. Adapter: input 100~240V,Output 5VDC/1.5A
	Ethernet	Used to connect the NVH300 to a host device. Adapter: input 100~240V,Output 5VDC/1.5A

*Test conditions: T=23°C; Illumination=300lux using incandescent lamp; sample printed barcodes made by Newland.

**Test conditions: Scan Distance= (min. DOF + max. DOF)/2; T=23°C; Illumination=300lux using incandescent lamp;

2D: QR Code; 10 Bytes; Resolution=15mil; PCS=0.8.

Specifications are subject to change without notice.

Version: V2.0 2026/3/3

Newland AIDC

Add: No.1 Rujiang West Rd.,
Mawei, Fuzhou, Fujian 350001, China
Tel: +86-591-83979500
Fax: +86-591-83979216
Email: info@newlandaidc.com
Web: www.newlandaidc.com

Asia Pacific

Add: 6 Raffles Quay #14-06
Singapore 048582
Email: info@newlandaidc.com

Europe & Middle East

Add: Rolweg 25, 4104 AV Culemborg,
The Netherlands
Tel: +31 (0) 345 87 00 33
Email: sales@newland-id.com
Tech Support: tech-support@newland-id.com

North America & Latin America

Add: 46559 Fremont Blvd.,
Fremont, CA 94538, USA
Tel: +1 510 490 3888
Fax: +1 510 490 3887
Email: info@newlandaidc.com